



**Product Installation Guidelines**

Version 1, 7<sup>th</sup> November 2023, Page 1 of 2

# GalvinCare® CP-BS™ Lead Safe Prison Ezy-Grip Shower Set w/ Vandal Resistant Shower

**PRODUCT CODE:  
121.51.13.03**



*For Watermark and/or WELS information of KITS, refer to each individually certified component.*

Item Codes:	Description	Watermark	WELS
<b>121.51.13.03</b>	<b>GalvinCare® CP-BS Lead Safe™ Prison Ezy-Grip Shower Set w/ Vandal Resistant Shower</b>	*	*
Components:			
121.33.64.00	GalvinCare® CP-BS Lead Safe™ Mental Health Anti-Ligature Wall Mtd Shower Rose 65 - Std	YES	YES
121.01.03.01	Safe-Cell® CP-BS Lead Safe™ Prison Ezy-Grip Wall Top Ass Complete Cold C/D	YES	N/A
121.01.03.02	Safe-Cell® CP-BS Lead Safe™ Prison Ezy-Grip Wall Top Ass Complete Hot C/D	YES	N/A

**Notes:**

1. N/A—Not applicable.
2. \* — The item is a **KIT**.
3. An electronic copy of each component’s Installation Instructions can either be downloaded from [www.galvinengineering.com.au](http://www.galvinengineering.com.au) or found inside the packaging.
4. Kit components may be purchased separately.

## INSTALLATION

**INSTALLATION COMPLIANCE:** Galvin Engineering products must be installed in accordance with these installation instructions and in accordance with AS/NZS 3500, the PCA and your local regulatory requirements. Water and/or electrical supply conditions must also comply to the applicable national and/or state standards. Failing to comply with these provisions shall void the product warranty and may affect the performance of the product.

**IMPORTANT:** Whilst our product designs take into account a broad range of installation types and surfaces, it is important that surfaces which fixtures are mounted to are flat and free from defect. This is especially important when installing product ranges that have been designed for correctional and health facilities, where special attention is required to minimise ligature points and areas for concealment of contraband. In addition to ensuring the products are fitted securely and in accordance with the following instructions, consideration shall be given to the use of non-pick mastics such as BASF Sonolastic “Ultra” to ensure a high quality and safe installation.

**TROUBLESHOOTING**

PROBLEM	CAUSE	RECTIFICATION
Dripping water on tap	Ceramic cartridge is worn or damaged	Remove and inspect the cartridge, remove debris and /or replace cartridge if damaged
Water not flowing from tap	Water supply is turned off	Turn on water supply
Dripping water on shower	Headworks are worn or damaged	Remove and inspect the headworks, remove debris and/or replace head parts if damaged
Inconsistent flow	Flow restrictor is blocked	Remove flow regulator from body and remove debris. Install an in-line strainer to stop further blockages.
Leak from behind body	Sealant is insufficient	Apply more sealant
Rate of flow inadequate	The flow restrictor may not be satisfactory due to inadequate supply pressure	Remove flow restrictor and replace with a flow restrictor of different capacity to suit (available from Galvin Engineering)

**WARRANTY**

Galvin Engineering products are covered under our Manufacturer's Warranty. Galvin Engineering products must be installed in accordance with the installation instructions and in accordance with AS 3500 and NCC Volume Three, relevant Australian Standards and local authorities applicable to product being installed. Water and electrical supply conditions must also comply to the applicable national and/or state standards, failing to comply with these provisions may void the product warranty and affect performance of the product.

Please visit [www.galvinengineering.com.au](http://www.galvinengineering.com.au) to view the full warranty, our Installation Compliance and Maintenance & Cleaning information as well as any other additional information.