

# Ezy-Wash® Wall Mounted Exposed Mixing Unit Type 77W

Specification Data Sheet



## Features

- Lever action handles with red and blue indicator buttons (yellow available on request).
- Quick action Hydroseal jumper valve SBA's.
- 400mm reach swivel spout with aerator.
- Finished in bright chrome plate for added durability and easy cleaning.

## To Specify

The AS/NZS 3718 WaterMark Approved Ezy-Wash® Wall Mounted Exposed Mixing Unit, complies to AS6400-2005, WELS rated to 3 Star and is supplied standard with a swivel aerated upswept outlet, 80mm long lever handle finished in a bright chrome plate.

### Code:

**TF77WC-ESS** - Ezy-Wash CP-BS Wall Mounted Exposed Mixing Unit Type 77 FI Inlet with 400 Reach.



A family  
owned  
Australian  
business




**galvin**specialised  
commercial taps + fixtures

## Performance Standards & Approvals

- AS/NZS 3718 - WaterMark
- WELS 3 Star Rating



## Typical Dimensions



## Technical Information

- Inlet: 1/2" BSP - Female
- Outlet: Aerator
- Headworks: Jumper Valve
- Working Pressure Range (kPa): 100 Min - 500 Max
- Maximum Working Temperature (°C): 5 Min - 80 Max
- Nominal Flow Rate: 9
- Construction: DZR Brass
- Finish: Chrome

## Maintenance & Cleaning

Galvin Specialised products should be cleaned with a soft damp cloth using only mild liquid detergent or soap and water. Do not use cleaning agents containing a corrosive acid, scouring agent or solvents. Do not use cream cleaners, as they are abrasive. Use of unsuitable cleaning agents may damage the surface. Any damage caused in this way will not be covered by warranty.

Regular maintenance should be carried out in accordance with the installation and troubleshooting guides provided with the product, relevant Australian Standards, local authorities and state codes.

As part of maintaining a safe and reliable plumbing system, we recommend tapware and valves are operated on at least a daily basis.

## Warranty

Galvin Specialised products are covered under our Manufacturer's Warranty at [www.galvinengineering.com.au](http://www.galvinengineering.com.au). Galvin Specialised products must be installed in accordance with the installation instructions and in accordance with AS3500 and the PCA, relevant Australian Standards and local authorities applicable to product being installed. Water and electrical supply conditions must also comply to the applicable national and/or state standards, failing to comply with these provisions may void the product warranty and affect performance of the product.

Whilst all reasonable care has been taken in compiling the information in this document, the designs, dimensions and products shown are indicative only and should not be relied upon without our prior approval. Due to our policy of continuous development, we reserve the right to alter any details of specifications or products without notice. All information, drawings, technical specifications and product designs remains the property of Galvin Engineering Pty Ltd.

410 Victoria Rd, Malaga, WA 6090  
 Within Australia: **1300 514 074** Outside Australia: P: +61 (0)8 9249 5900  
 F: +61 (0)8 9249 5916  
[sales@galvinengineering.com.au](mailto:sales@galvinengineering.com.au)  
[www.galvinengineering.com.au](http://www.galvinengineering.com.au)

ABN: 78 008 719 382

PERTH | SYDNEY | MELBOURNE | BRISBANE | ADELAIDE

A business unit of

**GalvinEngineering**   
 the mark of reliability