

Product Installation Guidelines

Version 1.2, 11 March 2025, Page 1 of 4 Document No.: 001.00.30.25

CP-BS Lead Safe Wall Trough Outlets w/ Vandal Resistant Aerator





PRODUCTS				
		WELS	Water	Nominal
Item Code	Description	Rating	Consumption	Flow Rate
167.93.11.01	Galvinlab [®] CP-BS Lead Safe [™] Wall Trough Outlet 165 with Vandal Resistant Aerator	6*	3.5	3.41
167.93.21.01	CP-BS Lead Safe [™] Wall Trough Outlet 225 with Vandal Resistant Aerator	5	5.0	4.9
*O - months and due to the sector of the sec				

*Components are dual-star rated. See "Dual-Star Rated Items" table for more information

SPECIFICATIONS

- Fitted with Vandal Resistant Aerator.
- Finished in bright chrome plate for easy cleaning and durability.
- Lead Safe[™] brass construction*

IMPORTANT: All outlets are tested in accordance with AS 3718 and leave our premises in good working order.

*Our Lead Safe™ product range is compliant with the Lead Free Requirements of the NCC 2022 Vol. Three, Clause A5G4(2) and NSF/ANSI 372. **Any flow controller incorporated in the outlet to be tightened to prevent removal by hand. As Per AS3718.

WARNINGS: Special attentions to be paid on notes, photos, images, or drawings of assembly steps marked with the warning symbol.

TECHNICAL DATA					
Inlet	G ½ – Female				
Outlet	Laminar Flow Aerator				
Werking Pressure Dange (I/De)	Min	50			
Working Pressure Range (KPa)	Max	500			
Working Tomperature Dange (%C)	Min	5			
working remperature Range (C)	Max	65			
Finish	Chrome				
NOTE: Galvin Engineering continually strives to improve their products. Specifications may change without					

notice.

DIMENSIONS



INSTALLATION

INSTALLATION COMPLIANCE: Galvin Engineering products must be installed in accordance with these installation instructions and in accordance with AS/NZS 3500, the PCA and your local regulatory requirements. Water and/or electrical supply conditions must also comply to the applicable national and/or state standards. Failing to comply with these provisions shall void the product warranty and may affect the performance of the product.



Dual-Star Rated Items (WELS)

Due to some state requirements, items are required to be in higher star rating (6-star). Therefore, for some items, two flow regulators are supplied. Primarily, the higher star-rated flow regulator is equipped in the assembly.

Items	Primary Flow Regulator	Alternative Flow regulator
167.93.11.01	6-stars (blue)	5-stars (orange)

REPLACING FLOW REGULATOR Image: shown. <tr

3. Reassemble

- Reverse step 1 to reassemble ensuring correct orientation.
- Test for leaks and correct operation

TROUBLESHOOTING					
PROBLEM	CAUSE	RECTIFICATION			
No water flow	Obstruction on spout	Check if there are obstructions hindering the water flow in the spout and take it out.			

WARRANTY

Galvin Engineering products are covered under our Manufacturer's Warranty. Galvin Engineering products must be installed in accordance with the installation instructions and in accordance with AS 3500 and NCC Volume Three, relevant Australian Standards and local authorities applicable to product being installed. Water and electrical supply conditions must also comply to the applicable national and/or state standards, failing to comply with these provisions may void the product warranty and affect performance of the product.

Please visit www.galvinengineering.com.au to view the full warranty, our Installation Compliance and Maintenance & Cleaning information as well as any other additional information.

Within Australia: 1300 514 074 Outside Australia: P: +61 (0)8 9338 2344 F: +61 (0)8 9338 2340 sales@galvinengineering.com.au www.galvinengineering.com.au ABN: 78 008 719 382 PERTH I SYDNEY I MELBOURNE I BRISBANE I ADELAIDE

