

Product Installation Guidelines & Scope of Use

Version 3.1, 11 March 2025, Page 1 of 6 Document No: 170.10.43.01

Ezy-Drink[®] Lead Safe™ Mini Push Button Drinking Bubbler Tap

PRODUCT CODES:

- 170.10.43.01

SPECIFICATIONS

- Easy to use push button mechanism automatically springs closed when it is not being used, saving money with reduced water wastage.
- A very robust tap for use in public applications where vandalism can be an issue.
- Chrome plate finish for easy cleaning and added durability.
- Lead Safe[™] brass construction

IMPORTANT: All Ezy-Drink[®] Bubbler taps are tested in accordance with AS 3718 and leave our premises in good working order.

*Our Lead Safe™ product range is compliant with the Lead-Free Requirements of the NCC 2022 Vol. Three, Clause A5G4(2) and NSF/ANSI 372. ** Any flow controller incorporated in the outlet to be tightened to prevent removal by hand. As Per AS3718.

WARNINGS: Special attention to be paid on notes, photos, images, or drawings of assembly steps marked with the warning symbol.



TECHNICAL DATA

Inlet		G 1⁄2" - Male		
Outlet		Metal Mouthguard		
Headwork		Push Button		
Working Processo Ronge (kPo)	Min	100		
working Pressure Range (KPa)	Max	500		
	Min	5		
working remperature Range (°C)	Max	60		
Nominal Flow Rate (LPM)		1.95		
Finish		Chrome		

NOTE: Galvin Engineering continually strive to improve their products. Specifications may change without notice.

TOOLS REQUIRED

- Spanner or adjustable crescent

- Thread tape

PRE-INSTALLATION - DIMENSIONS



prior to drinking taps to eliminate any foreign material.

INSTALLATION

INSTALLATION COMPLIANCE: Galvin Engineering products must be installed in accordance with these installation instructions and in accordance with AS/NZS 3500, the PCA and your local regulatory requirements. Water and/or electrical supply conditions must also comply to the applicable national and/or state standards. Failing to comply with these provisions shall void the product warranty and may affect the performance of the product.





REPLACING TOP ASSEMBLY - 170.73.43.00 (sold separately)





SERVICING TOP ASSEMBLY - 170.93.01.90 (sold separately)





TROUBLESHOOTING			
PROBLEM	CAUSE	RECTIFICATION	
Inconsistent flow	Blocked top assembly	Remove top assembly and clean	
Water is not flowing from tap	Water is turned off	Turn on water	
Button hard to press	The mains pressure may be too great	Reduce to below 500kPa (70PSI).	
Assembly leaking	Tap installed incorrectly	Follow installation steps ensuring thread tape is used when connecting water.	

WARRANTY

Galvin Engineering products are covered under our Manufacturer's Warranty. Galvin Engineering products must be installed in accordance with the installation instructions and in accordance with AS 3500 and NCC Volume Three, relevant Australian Standards and local authorities applicable to product being installed. Water and electrical supply conditions must also comply to the applicable national and/or state standards, failing to comply with these provisions may void the product warranty and affect performance of the product.

Please visit <u>www.galvinengineering.com.au</u> to view the full warranty, our Installation Compliance and Maintenance & Cleaning information as well as any other additional information.

Within Australia: 1300 514 074 Outside Australia: P: +61 (0)8 9338 2344 F: +61 (0)8 9338 2340 sales@galvinengineering.com.au www.galvinengineering.com.au ABN: 78 008 719 382 PERTH I SYDNEY I MELBOURNE I BRISBANE I ADELAIDE

