


## Product Installation Guidelines

Version 2, 4 June 2024, Page 1 of 4

# Ezy-Drink® CP-BS Lead Safe™ Wall Mounted Lever Action Bottle Filler

## PRODUCT CODES:

- 170.53.14.00



## SPECIFICATIONS

- Bottle filler taps are designed to operate at full mains pressure.
- Adjustable built-in flow restrictor.
- Made from Lead Safe™ DR Brass\*

**IMPORTANT:** All Ezy-Drink® lever bottle filler taps are tested in accordance with AS/NZS 3718 and leave our premises in good working order.

\*Our Lead Safe™ product range is compliant with the Lead Free Requirements of the NCC 2022 Vol. Three, Clause A5G4(2) and NSF/ANSI 372.

**WARNINGS:** Special attention to be paid on notes, photos, images, or drawings of assembly steps marked with the warning symbol.



## TECHNICAL DATA

|                                |                |     |
|--------------------------------|----------------|-----|
| Inlet                          | Rp 1/2"        |     |
| Outlet                         | Water diffuser |     |
| Headwork                       | Lever action   |     |
| Working Pressure Range (kPa)   | Min            | 50  |
|                                | Max            | 500 |
| Working Temperature Range (°C) | Min            | 5   |
|                                | Max            | 60  |
| Nominal Flow Rate (LPM)        | 1.7            |     |
| Finish                         | Chrome         |     |

**NOTE:** Galvin Engineering continually strives to improve their products. Specifications may change without notice.


## TOOLS REQUIRED

- Power drill
- Spanner or adjustable crescent
- Screwdriver


## PRE-INSTALLATION

- If the mounting holes do not already exist, mark out and drill the holes in the wall/sheet, as shown below.

**⚠ Note:** Before installation, all lines must be flushed. We recommend that a line strainer be installed prior to drinking taps to eliminate any foreign material.




**⚠** Rough-in Dimensions




## INSTALLATION

**IMPORTANT:** Galvin Engineering products must be installed in accordance with these installation instructions and in accordance with AS/NZS 3500, the PCA and your local regulatory requirements. Water and/or electrical supply conditions must also comply to the applicable national and/or state standards. Failing to comply with these provisions shall void the product warranty and may affect the performance of the product.




### 1. Fit tap assembly

- Fit wall plugs to wall as per dimensions above.
- When applying thread tape or sealant to the inlet, ensure the opening is not blocked. Failure to do so may cause the regulating screw to be blocked, which will affect the flow of water.
- Screw tap onto existing spud until the flange is touching the wall.
- Ensure the outlet is in the correct position and the holes in the flange align with the wall plugs.



### 2. Secure the body

- Secure the body with supplied screws.



### 3. Testing

- Once fitted, test the bottle filler tap for leaks and correct operation.
- To adjust water flow (if required)
  1. Remove the blanking screw.
  2. Adjust the water height by turning the regulating screw.
  3. Replace blanking screw.

**⚠ Note: The full range from minimum flow to maximum flow is only ¼ turn**

**TROUBLESHOOTING**

| PROBLEM                       | CAUSE   | RECTIFICATION   |
|-------------------------------|---|---|
| Inconsistent flow             | Blocked top assembly                                    | Remove top assembly and clean   |
| Water is not flowing from tap | Water is turned off                                     | Turn on the water   |
|                               | Blocked flow regulating screw                           | Remove flow regulating screw and clean                                  |
| Continuous flow               | Top assembly loose or internally obstructed or damaged  | Remove top assembly, clean with water, and regrease spindle if required |
| Rate of flow inadequate       | The flow regulating screw may not be adjusted correctly | Remove blanking screw and adjust flow regulating screw as described     |

**WARRANTY**

Galvin Engineering products are covered under our Manufacturer's Warranty. Galvin Engineering products must be installed in accordance with the installation instructions and in accordance with AS 3500 and NCC Volume Three, relevant Australian Standards and local authorities applicable to product being installed. Water and electrical supply conditions must also comply to the applicable national and/or state standards, failing to comply with these provisions may void the product warranty and affect performance of the product.

Please visit [www.galvinengineering.com.au](http://www.galvinengineering.com.au) to view the full warranty, our Installation Compliance and Maintenance & Cleaning information as well as any other additional information.